


K30RBT2XRH

Pick-to-Light – Placement Sensor

Capacitive Sensor




Technical data

Type	K30RBT2XRH
ID	3803588
Signal and display data	
Purpose	Pick-to-Light
Function	Touch Button
Light type	Red
LED service life (L70)	50000 h
Switch Function	Momentary
Features of color 2	Red, 1.7 lm
Special features	Wash down
Electrical data	
Operating voltage	12...30 VDC
DC rated operational current	≤ 150 mA
Max. current consumption per color	55 mA
Communication protocol	BannerBus (Pro Editor compatible)
Output function	NC contact, PNP/NPN
Input type	Bipolar (PNP/NPN)
Response time typical	< 150 ms
Mechanical data	
Design	Dome, K30
Dimensions	Ø 30 x 41 mm
Housing material	Plastic, PC, Black
Window material	Polycarbonate, diffuse
Electrical connection	Cable, 2 m, PVC
Number of cores	5

Features

- Protection classes IP67 IP69K
- Cable, 2 m
- Disabled: No color
- Enabled: Red (COL 2)
- Operating voltage 12...30 VDC
- PNP switching
- NO contact
- Capacitive sensor of the second generation
- High immunity to false actuation by splashing, detergents, oils and other contaminants

Wiring diagram



Functional principle

The K30 pick-and-place sensor is suitable for many assembly and placement sequences. LED light is reflected perfectly by the entire dome. The device has two display colors depending on the version: Color 1 Shows the disabled state, color 2 the enabled state. Since the device has no inputs, a color change is exclusively realized by touching the sensor (enable). Devices with a hold function keep the enabled state, even when the contact ends.

Technical data

Ambient temperature	-40...+50 °C
Relative humidity	0...90 %
Protection class	IP67 IP69
Tests/approvals	
Approvals	CE, cULus listed

Accessories

SMB22A	3079414
--------	---------

Mounting bracket, stainless steel, for
K30L series

