


# PKG3M-2-RSC4T/TXL1001

## Weld-Splatter Resistant Actuator and Sensor Cable – Extension Cable



### Technical data


|                              |                                                              |
|------------------------------|--------------------------------------------------------------|
| Type                         | PKG3M-2-RSC4T/TXL1001                                        |
| ID                           | 6628399                                                      |
| Connector A                  | Female, M8 × 1, Straight                                     |
| Number of Pins               | 3                                                            |
| Contacts                     | Brass, CuZn, Gold-plated                                     |
| Contact carriers             | Plastic, TPU, Black                                          |
| Connector body               | Plastic, TPU, Black                                          |
| Coupling nut/screw           | Brass, CuZn, Nickel-plated                                   |
| Seal                         | Plastic, FPM/FKM                                             |
| Tightening torque (range)    | 0.5 ... 0.6 Nm<br>(observe max. torque of mating connector!) |
| Mechanical lifespan          | > 100 Mating cycles                                          |
| Pollution degree             | 3                                                            |
| Protection class             | IP67, IP69K, Only in screwed condition                       |
| Connector B                  | Male, M12 × 1, Straight, A-coded                             |
| Number of pins               | 3                                                            |
| Contacts                     | Brass, CuZn, Gold-plated                                     |
| Contact carriers             | Plastic, TPU, Black                                          |
| Connector body               | Plastic, TPU, Black                                          |
| Coupling nut/retaining screw | Brass, CuZn, Nickel-plated                                   |
| Mechanical life              | > 100 Mating cycles                                          |
| Pollution degree             | 3                                                            |
| Protection class             | IP67, IP69K, Only when screwed together                      |
| Cable                        |                                                              |
| Cable diameter               | Ø 4.9 mm ±0.20                                               |

### Features



- M8 female, straight, 3-pin
- Male M12, straight, 3-pin
- Jacket material: PUR jacketed with aramid fibers
- Jacket color: yellow
- Resistant to welding sparks
- Flame retardant
- Resistant to chemicals, UV radiation and oils
- Free from halogen, silicone, PVC and LABS
- Protection class: IP67, IP69K
- Protective jacket material: aramid fibers
  - Tensile strength: 2923 MPa
  - Breaking strength: 333 N
  - Elongation at break: 3.6 %
  - Temperature peaks: up to +200 °C
- Cable length: 2.0 m

### Cable Cross-Section




Technical data

|                                          |                                        |
|------------------------------------------|----------------------------------------|
| Cable length                             | 2 m                                    |
| Cable jacket                             | PUR, Yellow                            |
| Core insulation                          | PP                                     |
| Core cross-section                       | 3 x 0.34 mm <sup>2</sup>               |
| Arrangement of strands                   | 42 x 0.1 mm                            |
| Core colors                              | BN, BU, BK                             |
| Electrical properties at +20 °C          |                                        |
| Rated voltage                            | 50 V <sub>AC</sub> /60 V <sub>DC</sub> |
| Test voltage                             | 2000 V                                 |
| Current                                  | 4 A                                    |
| Insulation resistance                    | > 30.5 MΩ/km                           |
| forward resistance                       | max. 57 Ω/km                           |
| Mechanical and chemical properties       |                                        |
| Bending radius (stationary installation) | ≥ 5 x Ø                                |
| Bending radius (flexible use)            | ≥ 10 x Ø                               |
| Ambient temperature range (stationary)   | -50...+105 °C                          |
| Ambient temperature range (In motion)    | -30...+90 °C                           |


Accessories

|                                                                                                                       |         |
|-----------------------------------------------------------------------------------------------------------------------|---------|
| TORQUE-WRENCH-SET-AS                                                                                                  | 6936170 |
| Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14) |         |

Accessories

|                                                                                     |                       |           |                                                                                                                                                                            |
|-------------------------------------------------------------------------------------|-----------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimension drawing                                                                   | Type                  | ID        |                                                                                                                                                                            |
|  | LABEL-HOLDER-FLEX-PVC | 100048170 | PVC label holder for identification of extension cables (TEL/TXL product series); for cable diameters: min. 5 mm; dimensions 4 x 18 mm; delivery unit: 50 pcs. per package |

Contact assignment



Circuit Diagram

