


Q40RW3FF400Q1 Photoelectric Sensor – Diffuse Mode Sensor with Fixed-Field Background Suppression




Technical data

Туре	Q40RW3FF400Q1
ID no.	3033389
Optical data	
Function	Proximity switch
Operating mode	Background suppression, non-adjustable
Light type	IR
Wavelength	880 nm
Range	0400 mm
Electrical data	
Operating voltage	20250 VAC
AC rated operational current	≤ 200 mA
Output function	Dark operation, Relay output
Switching frequency	≤ 40 Hz
Readiness delay	≤ 100 ms
Response time typical	< 16 ms
Mechanical data	
Design	Rectangular, Q40
Dimensions	Ø 30 x 46 x 40.1 x 82.5 mm
Housing material	Plastic, Thermoplastic material
Lens	plastic, Polycarbonate
Electrical connection	Connectors, 1/2", PVC
Number of cores	4
Ambient temperature	-40+70 °C
Protection class	IP69
Special features	Encapsulated Wash down

Features

- ■M12 × 1 Micro male connector (AC), 4-pin
- Protection classes IP67/IP69K
- Ambient temperature: -40 °C...+70 °C

Wiring diagram




Functional principle

The emitter and receiver are incorporated in a single housing. The light reflection of the target is detected and triggers the sensor to switch. Thus the switching distance largely depends on the reflectivity of the target.

Excess gain curve

Excess gain in relation to the distance






Technical data

Power-on indication	LED, Green
Switching state	LED, Yellow
Excess gain indication	LED
Tests/approvals	
MTTF	448 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE, UL, CSA

Accessories




3032723 Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread




Mounting bracket, stainless steel, for M10 x 1.5 thread, thread length 30 mm

3011185

3073135



3052521 Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable



Mounting bracket, stainless steel, for sensors with 30 mm thread