


CL50ZW


LED Indicator – Tower Light



Features

- LED tower light
- Individually controllable
- Mechanical screw-in thread M30x1.5
- Protection class IP67
- Monochrome: White (COL 1)
- Operating voltage: 85...264 VAC

Wiring diagram



Functional principle

Multicolor/multifunction display
Rugged and well-priced LED tower, easy to install
Illuminated segments for clear operator guidance and display of system status.
Display of up to 3 colors.
Compact devices, no controller required
No mounting

Technical data

Type	CL50ZW
ID	3085751
Signal and display data	
Purpose	LED indicator light
Function	Tower light
Light type	White
LED service life (L70)	50000 h
Dimmable	No
Features of color 1	White, Permanently on, 85 lm
Electrical data	
Operating voltage	85...264 VAC
AC rated operational current	≤ 80 mA
Max. current consumption per color	60 mA
Input type	AC
Response time typical	< 500 ms
Mechanical data	
Cascadable	No
Design	Smooth barrel, CL50Z
Dimensions	Ø 50 x 183.2 mm
Housing material	Plastic, ABS/Polycarbonate, Black
Window material	Polycarbonate, diffuse
Electrical connection	Cable, 2 m, PVC
Number of cores	4
Ambient temperature	-40...+50 °C
Relative humidity	0...95 %
Protection class	IP67

Technical data

Tests/approvals	
Approvals	CE, UL listed