


RES-180S6S-8BAR-H1151/N0

Absolute Rotary Encoder - Single-Turn Industrial Line






Features

- Synchro flange, Ø 36 mm
- Solid shaft, Ø 6 mm × 12.5 mm
- Magnetic measuring principle
- Shaft material: stainless steel
- Protection class IP67 on housing and shaft side
- -40...+85 °C
- Max. 4000 rpm (continuous operation 2000 rpm)
- 15...30 VDC
- Analog output 0...10 V
- Counting mode CW
- M12 × 1 male connector, 5-pin
- 360° resolved in 12 bit (4096 positions)

Technical data

Type	RES-180S6S-8BAR-H1151/N0
ID	100016359
Measuring principle	Magnetic
General data	
Max. Rotational Speed	4000 rpm
Starting torque	< 0.01 Nm
Measuring range	0...360 °
Repetition accuracy	± 0.2 ° At 25 °C
Absolute accuracy	± 1 ° At 25 °C
Output type	Absolute singleturn
Resolution singleturn	12 Bit
Electrical data	
Operating voltage	15...30 VDC
No-load current	35 mA
Short-circuit protection	yes
Output function	Analog output
Voltage output	0...10 V
Mechanical data	
Design	Solid shaft
Flange type	Synchro flange
Flange diameter	Ø 36 mm
Shaft Type	Solid shaft
Shaft diameter D [mm]	6
Shaft Length L [mm]	12.5
	Shaft with surface
Shaft material	Stainless steel

Wiring diagram



Technical data


Housing material	Die-cast zinc
Electrical connection	Connector, M12 × 1
Axial shaft load	20 N
Radial shaft load	40 N
Environmental conditions	
Ambient temperature	-40...+85 °C
Vibration resistance (EN 60068-2-6)	300 m/s², 10...2000 Hz
Shock resistance (EN 60068-2-27)	2500 m/s², 6 ms
Protection class	IP67
Protection class shaft	IP67

Accessories

RCS-15-06-06

1545362


Bellows coupling, outer diameter:
15 mm, bore diameter: 6 mm/6 mm



RCS-19-06-06

1545360


Bellows coupling, outer diameter:
19 mm, bore diameter: 6 mm/6 mm



RCS-19-10-06

1545358

Bellows coupling, outer diameter:
19 mm, bore diameter: 10 mm/6 mm



RCS-15-08-06

1545361

Bellows coupling, outer diameter:
15 mm, bore diameter: 8 mm/6 mm

