


# Q20PRL Photoelectric Sensor – Opposed Mode Sensor (Emitter/Receiver)



#### Technical data


Туре	Q20PRL
ID no.	3078272
Optical data	
Function	Opposed mode sensor
Operating mode	Receiver
Range	020000 mm
Electrical data	
Operating voltage	1030 VDC
Residual ripple	< 10 % U <sub>ss</sub>
DC rated operational current	≤ 100 mA
No-load current	≤ 18 mA
Reverse polarity protection	yes
Output function	Complementary contact, PNP
Switching frequency	≤ 600 Hz
Readiness delay	≤ 100 ms
Response time typical	< 1 ms
Mechanical data	
Design	Rectangular, Q20
Dimensions	20 x 12 x 32 mm
Housing material	Plastic, Thermoplastic material
Lens	plastic, Acrylic
Electrical connection	Cable, 2 m, PVC
Number of cores	4
Core cross-section	0.35 mm²
Ambient temperature	-20+60 °C
Protection class	IP67



#### **Features**

- ■Cable, PVC, 2 m
- ■Protection class IP67
- ■LED all-round visible
- Operating voltage: 10...30 VDC
- ■PNP switching output, changeover

## Wiring diagram



# Functional principle


Opposed mode sensors consist of an emitter and receiver. They are installed opposite each other so that the light from the emitter is aimed directly at the receiver. When an object interrupts or weakens the light beam, the sensor switches. Opposed mode sensors are the most reliable photoelectric sensors for detection of opaque targets. An excellent contrast between light and dark conditions and an extremly high excess gain are typical of this sensing mode, thus allowing operation over larger distances and under difficult conditions.



## Technical data

Power-on indication	LED, Green
Switching state	LED, Yellow
Error indication	LED, green, Flashing
Excess gain indication	LED, yellow, flashing
Tests/approvals	
Approvals	CE


## **Excess Gain Curve**



# Accessories

SMBQ20H 3079041

Mounting bracket, stainless steel, horizontally mounted, for Q20



3079040 Mounting bracket, stainless steel, rectangular, for Q20

3,4 x 9,4 31,2 36

Mounting bracket, stainless steel, rectangular, for Q20

3079042



3079043

Protective housing, stainless steel, for