


# RSSD-RSSD-4422-40M

## Industrial Ethernet Cable – Extension Cable



### Technical data

|                              |                                                            |
|------------------------------|------------------------------------------------------------|
| Type                         | RSSD-RSSD-4422-40M                                         |
| ID                           | 6635378                                                    |
| Connector A                  | Male, M12 × 1, Straight, D-coded                           |
| Number of Pins               | 4                                                          |
| Contacts                     | Metal, CuZn, Gold-plated                                   |
| Contact carriers             | Plastic, TPU, Black                                        |
| Connector body               | Plastic, TPU, Black                                        |
| Coupling nut/screw           | Brass, CuZn, Nickel-plated                                 |
| Tightening torque (range)    | 0.8 ... 1 Nm<br>(observe max. torque of mating connector!) |
| Mechanical lifespan          | > 100 Mating cycles                                        |
| Pollution degree             | 3                                                          |
| Protection class             | IP67, Only in screwed condition                            |
| Connector B                  | Male, M12 × 1, Straight, D-coded                           |
| Number of pins               | 4                                                          |
| Contacts                     | Metal, CuZn, Gold-plated                                   |
| Contact carriers             | Plastic, TPU, Black                                        |
| Connector body               | Plastic, TPU, Black                                        |
| Coupling nut/retaining screw | Brass, CuZn, Nickel-plated                                 |
| Tightening torque            | 0.8 ... 1 Nm (observe max. torque of mating connector!)    |
| Mechanical life              | > 100 Mating cycles                                        |
| Pollution degree             | 3                                                          |
| Protection class             | IP67, Only when screwed together                           |
| Cable                        |                                                            |
| Network protocol             | Ethernet                                                   |
| Cable diameter               | Ø 6.5 mm ±0.20                                             |




### Features



- M12 male connector, straight, D-coded
- M12 male connector, straight
- Ethernet cable: 4-pin, AWG 22
- CAT 5E
- Jacket material: PUR
- Jacket color: green
- Shielding: overlapping aluminum foil, tinned copper wire
- Jacket diameter: 6.5 mm
- Suitable for drag chain use
- Oil resistant acc. to IEC 60811-2-1 and UL13
- Halogen free acc. to IEC 60754
- Flame retardant acc. to IEC 60332-1-2 and UL FT2
- RoHS compliant
- PNO compliant
- UL
- Cable length: 40 m

### Cable Cross-Section



Technical data

|                                          |                                   |
|------------------------------------------|-----------------------------------|
| Cable length                             | 40 m                              |
| Cable jacket                             | PUR, Green                        |
| Shielding                                | Aluminum foil, tinned copper wire |
| Core insulation                          | TPE-O                             |
| Core cross-section                       | 4 x 0.32 mm <sup>2</sup>          |
| Arrangement of strands                   | 7 x 0.25 mm                       |
| Core colors                              | WH, YE, BU, OG                    |
| Electrical properties at +20 °C          |                                   |
| Rated voltage                            | 30 V                              |
| Test voltage                             | 2000 V                            |
| Current                                  | 4 A                               |
| DC resistance (loop)                     | 120 Ω/km                          |
| Nom. impedance                           | 100 Ω (1MHZ)                      |
| Nom. capacitance                         | 50 pF/m                           |
| Mechanical and chemical properties       |                                   |
| Bending radius (stationary installation) | ≥ 5 x Ø                           |
| Bending radius (flexible use)            | ≥ 15 x Ø                          |
| Bending cycles                           | ≥ 5 million                       |
| Torsional stress                         | ± 180 °/m                         |
| Torsion cycles                           | ≤ 100,000 Cycles                  |
| Ambient temperature range (stationary)   | -40...+80 °C                      |
| Ambient temperature range (In motion)    | -30...+80 °C                      |
| Other Features                           |                                   |
| Qualified for drag chain use             | yes                               |
| Halogen-free                             | yes                               |
| PVC-free                                 | yes                               |
| UV resistance                            | yes                               |
| Oil-resistant                            | yes                               |
| Flame-retardant                          | yes                               |
| Approvals                                | UL Listed                         |

Accessories

|                                                                                                                       |         |
|-----------------------------------------------------------------------------------------------------------------------|---------|
| TORQUE-WRENCH-SET-AS                                                                                                  | 6936170 |
| Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14) |         |

Contact assignment



Circuit Diagram

