


QS30RRXSH2O

Photoelectric Sensor – Opposed Mode Sensor (Emitter/Receiver)

For Water Detection




Technical data

Type	QS30RRXSH2O
ID no.	3083304
Optical data	
Function	Opposed mode sensor
Operating mode	Receiver
Range	0...8000 mm
Electrical data	
Operating voltage	10...30 VDC
Residual ripple	< 10 % U _{ss}
DC rated operational current	≤ 65 mA
Short-circuit protection	yes
Reverse polarity protection	yes
Output function	NO contact, dark operation, PNP/NPN
Readiness delay	≤ 100 ms
Response time typical	< 10 ms
Mechanical data	
Design	Rectangular with thread, QS30
Dimensions	Ø 30 x 54.3 x 22 x 53 mm
Housing material	Plastic, Thermoplastic material, Yellow
Lens	plastic, Acrylic
Electrical connection	Cable, 2 m, PVC
Number of cores	5
Core cross-section	0.5 mm ²
Ambient temperature	-20...+60 °C

Features

- Cable, PVC, 2 m
- Protection class IP67
- Cable, 2 m
- Super high-power water detection sensor
- Operating voltage: 10...30 VDC
- Switching output, bipolar, dark operation

Wiring diagram



Functional principle

The opposed mode sensor incorporates an emitter and a receiver. The emitter emits light in the near IR range with a wavelength of 1450 nm, which approximates one of the absorption edges of water. The resulting high contrast ratio leads to a particularly high sensitivity with water or media containing water as opposed to transparent media.

Technical data


Protection class	IP67
Special features	Encapsulated Water detection
Power-on indication	LED, Green
Switching state	LED, Yellow
Error indication	LED, green, Flashing
Excess gain indication	Bargraph, yellow, flashing
Tests/approvals	
Approvals	CE

Accessories

SMBQS30Y

3002811


Protective housing, stainless steel, for QS30 series



SMBQS30YL

3072741


Protective housing with safety glass panel, stainless steel, for QS30 series



SMB30A

3032723


Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread



SMBQS30L

3002809


Mounting bracket, stainless steel, for QS30 series



SMB30MM

3027162

Mounting bracket, rectangular, stainless steel, for sensors with 30 mm thread, wide holes for accurate alignment



SMB30SC

3052521

Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable

