


REM-101S6S-9F32B-H1151

Absolute Rotary Encoder - Multiturn Industrial Line





Features

- Synchro flange, Ø 36 mm
- Solid shaft, Ø 6 mm × 12.5 mm
- Magnetic measuring principle
- Shaft material: stainless steel
- Protection class IP67 on housing and shaft side
- -40...+80 °C
- Max. 4000 rpm (continuous operation 2000 rpm)
- 10...30 VDC
- SAE J1939
- M12 × 1 male connector, 5-pin
- Singleturn resolution 14 bit scalable, default 14 bit
- Multiturn resolution scalable up to 29 bit over total resolution, default 18 bit
- Total resolution 32 bit scalable, default: 32 bit

Technical data

Type	REM-101S6S-9F32B-H1151
ID	100023543
Measuring principle	Magnetic
General data	
Max. Rotational Speed	4000 rpm
Starting torque	< 0.01 Nm
Repetition accuracy	± 0.2 ° At 25 °C
Absolute accuracy	± 1 ° At 25 °C
Output type	Absolute multiturn
Electrical data	
Operating voltage	10...30 VDC
No-load current	80 mA
Short-circuit protection	yes
Wire breakage/Reverse polarity protection	yes
Communication protocol	SAE J1939
Interface	SAE J1939
Mechanical data	
Design	Solid shaft
Flange type	Synchro flange
Flange diameter	Ø 36 mm
Shaft Type	Solid shaft
Shaft diameter D [mm]	6
Shaft Length L [mm]	12.5
	Shaft with surface
Shaft material	Stainless steel

Wiring diagram




Technical data

Housing material	Die-cast zinc
Electrical connection	Connector, M12 × 1
Axial shaft load	20 N
Radial shaft load	40 N
Environmental conditions	
Ambient temperature	-40...+80 °C
Vibration resistance (EN 60068-2-6)	300 m/s², 10...2000 Hz
Shock resistance (EN 60068-2-27)	2500 m/s², 6 ms
Protection class	IP67
Protection class shaft	IP67

Accessories


RCS-15-06-06	1545362
--------------	---------

Bellows coupling, outer diameter:
15 mm, bore diameter: 6 mm/6 mm




RCS-19-06-06	1545360
--------------	---------

Bellows coupling, outer diameter:
19 mm, bore diameter: 6 mm/6 mm




RCS-19-10-06	1545358
--------------	---------

Bellows coupling, outer diameter:
19 mm, bore diameter: 10 mm/6 mm



RCS-15-08-06	1545361
--------------	---------

Bellows coupling, outer diameter:
15 mm, bore diameter: 8 mm/6 mm



Accessories

Dimension drawing	Type	ID
	RKC5701-5M	6931034



Bus cable for CAN (DeviceNet, -
CANopen), M12 female connector,
straight, cable length: 5 m, jacket
material: PUR, anthracite; cULus
approval