


TL30FGGGYRQ


LED Indicator – Multicolor/Multifunction Display



Features

- Plastic housing, black
- EMI and RFI immune
- Protection class IP65
- M12 x 1 connector
- Colors: Green (COL 1) / Green (COL 2) / Green (COL 3) / Yellow (COL 4) / Green (COL 5)
- Operating voltage: 18...30 VDC or 24 VAC with 45 mA per LED color
- Inputs: PNP/NPN

Wiring diagram



Functional principle

Flat multicolor/multifunction display
 Rugged and well-priced LED tower, easy to install
 Illuminated segments for clear operator guidance and display of system status
 Display of up to 5 colors
 Compact devices, no controller required
 No mounting
 The wiring diagram shows a PNP pin assignment

Technical data


| | |
|------------------------------------|--|
| Type | TL30FGGGYRQ |
| ID | 3025874 |
| Signal and display data | |
| Purpose | LED indicator light |
| Function | Tower light |
| Light type | Green Green Green Yellow Red |
| Dimmable | No |
| Features of color 1 | Green, Permanently on |
| Features of color 2 | Green |
| Features of color 3 | Green |
| Features of color 4 | Yellow |
| Features of color 5 | Red |
| Electrical data | |
| Operating voltage | 18...30 VDC |
| DC rated operational current | ≤ 18 mA |
| Operating voltage | 21...27 VAC |
| Max. current consumption per color | 18 mA |
| Input type | Bipolar (PNP/NPN) |
| Response time typical | < 1 ms |
| Mechanical data | |
| Cascadable | No |
| Design | Rectangular, TL30F |
| Dimensions | 204.3 x 30 x 19.1 mm |
| Housing material | Metal, AL |

Technical data

| | |
|------------------------|-------------------------------|
| | Thermoplastic material, Black |
| Window material | Acrylic, diffuse |
| Electrical connection | Connector, M12 × 1, PVC |
| Number of cores | 8 |
| Ambient temperature | -40...+50 °C |
| Relative humidity | 0...95 % |
| Protection class | IP65 |
| Tests/approvals | |
| Approvals | CE |


Accessories

SMBPVA1 3056884



Mounting bracket, for PVA and PVD, stainless steel; set consisting of two brackets and screws

SMBPVA2 3054451




Mounting bracket, for PVA and PVD, for mounting on 28 mm pipes, 4 brackets (2 per sensor) included in delivery

Accessories

| Dimension drawing | Type | ID | |
|-------------------|------|----|--|
|-------------------|------|----|--|



| | | |
|-------------|---------|---|
| RKC8T-2/TEL | 6625130 | Connection cable, M12 female connector, straight, 8-pin, cable length: 2 m, jacket material: PVC, black; cULus approval |
|-------------|---------|---|



| | | |
|-------------|---------|---|
| WKC8T-2/TEL | 6625133 | Connection cable, M12 female connector, angled, 8-pin, cable length: 2 m, jacket material: PVC, black; cULus approval |
|-------------|---------|---|