


# WKS12T-10/TEL

## Actuator and Sensor Cable, PVC – Connection Cable




### Features




- Female M12, angled, 12-pin
- Shield on coupling nut/screw
- Jacket material: PVC, shielded
- Jacket color: black
- Resistant to chemicals and oils
- Flame retardant
- Resistant to acids and alkaline solutions
- Resistant to microbes and hydrolysis
- LABS free
- Protection class: IP67, IP69K
- Cable length: 10 m

### Cable Cross-Section



### Contact assignment



### Functional principle

Drawing shows design status including hexagon coupling nut (Production start CW11/2016). Wiring diagram shows contact assignment acc. to DIN EN 60947-5-2 (Production start CW16/2017).

### Technical data

|                                 |                                                            |
|---------------------------------|------------------------------------------------------------|
| Type                            | WKS12T-10/TEL                                              |
| ID                              | 6626910                                                    |
| Connector A                     | Female, M12 × 1, Angled, A-coded                           |
| Number of Pins                  | 12                                                         |
| Contacts                        | Brass, CuZn, Gold-plated                                   |
| Contact carriers                | Plastic, TPU, Black                                        |
| Connector body                  | Plastic, TPU, Black                                        |
| Coupling nut/screw              | Brass, CuZn, Nickel-plated                                 |
| Seal                            | Plastic, FPM/FKM                                           |
| Mechanical lifespan             | > 100 Mating cycles                                        |
| Pollution degree                | 3                                                          |
| Protection class                | IP67, IP69K, Only in screwed condition                     |
| Cable                           |                                                            |
| Cable diameter                  | Ø 6.6 mm ±0.20                                             |
| Cable length                    | 10 m                                                       |
| Cable jacket                    | PVC, Black                                                 |
| Shielding                       | Aluminum foil, tinned copper wire                          |
| Core insulation                 | PVC                                                        |
| Core cross-section              | 12 x 0.14 mm²                                              |
| Arrangement of strands          | 18 x 0.1 mm                                                |
| Core colors                     | BN, WH, BU, BK, GY, PK, VT, OG, GY/PK, WH/BU, WH/GY, GY/BN |
| Electrical properties at +20 °C |                                                            |
| Rated voltage                   | 30 V                                                       |
| Test voltage                    | 2000 V                                                     |
| Current                         | 1.5 A                                                      |
| Insulation resistance           | > 30.5 MΩ/km                                               |
| forward resistance              | max. 138 Ω/km                                              |

Technical data

| Mechanical and chemical properties       |               |
|------------------------------------------|---------------|
| Bending radius (stationary installation) | ≥ 5 x Ø       |
| Bending radius (flexible use)            | ≥ 10 x Ø      |
| Ambient temperature range (stationary)   | -40...+105 °C |
| Ambient temperature range (In motion)    | 0...+80 °C    |
| Approvals                                | cULus         |

Circuit Diagram




Stranded Wire Colors

| Pin | DIN 47100 (old) | DIN EN 60947-5-2 (new) |
|-----|-----------------|------------------------|
| 1   | BN              | BN                     |
| 2   | BU              | WH                     |
| 3   | WH              | BU                     |
| 4   | GN              | BK                     |
| 5   | PK              | GY                     |
| 6   | YE              | PK                     |
| 7   | BK              | VT                     |
| 8   | GY              | OG                     |
| 9   | RD              | GY/PK                  |
| 10  | VT              | WH/BU                  |
| 11  | GY/PK           | WH/GY                  |
| 12  | RD/BU           | GY/BN                  |

Accessories

|                                                                                                                       |         |
|-----------------------------------------------------------------------------------------------------------------------|---------|
| TORQUE-WRENCH-SET-AS                                                                                                  | 6936170 |
| Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14) |         |

|                                                                                                                                         |         |
|-----------------------------------------------------------------------------------------------------------------------------------------|---------|
| BLANK-LABEL-FOR-CORDSETS-TEL-TXL                                                                                                        | 6936206 |
| Label for TEL and TXL cables, length: 18 mm, height: 4 mm, material: polycarbonate (PC), color: white, halogen-free and flame-retardant |         |



Accessories

| Dimension drawing | Type                  | ID        |                                                                                                                                                                            |
|-------------------|-----------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                   | LABEL-HOLDER-FLEX-PVC | 100048170 | PVC label holder for identification of extension cables (TEL/TXL product series); for cable diameters: min. 5 mm; dimensions 4 × 18 mm; delivery unit: 50 pcs. per package |