


REI-43H38S-4C1000-H1181

Incremental Encoder

Industrial Line




Features

- Flange without mounting element, Ø 100 mm
- Hollow shaft, Ø 38 mm
- Optical measuring principle
- Shaft material: stainless steel
- Protection class IP65 on housing and shaft side
- -40 ... +80 °C
- Max. 6000 rpm (at 60 °C: 2500 rpm)
- 10...30 VDC
- RS422/TTL invertible
- Pulse frequency max. 300 kHz
- M12 × 1 male connector, 8-pin
- 1000 pulses per revolution

Technical data

Type	REI-43H38S-4C1000-H1181
ID	100011447
Measuring principle	Optical
General data	
Max. Rotational Speed	6000 rpm
Moment of inertia of the rotor	220 × 10 ⁻⁶ kgm ²
Starting torque	< 0.2 Nm
Output type	Incremental
Resolution, incremental	1000 ppr
Electrical data	
Operating voltage	10...30 VDC
No-load current	120 mA
Output current	≤ 20 mA
Short-circuit protection	yes
Pulse frequency max.	300 kHz
Signal level high	min. 2.5 V
Signal level low	max. 0.5 V
Output function	RS422/TTL, invertable
Mechanical data	
Design	Hollow shaft
Flange type	Flange without mounting element
Flange diameter	Ø 100 mm
Shaft Type	Hollow shaft
Shaft diameter D [mm]	38
Shaft material	Stainless steel
Housing material	Die-cast zinc

Wiring diagram



Technical data


Electrical connection	Connector, M12 × 1
	8-pin
Environmental conditions	
Ambient temperature	-40...+80 °C
Vibration resistance (EN 60068-2-6)	10 g (100 m/s²), 10...2000 Hz
Shock resistance (EN 60068-2-27)	200 g (2000 m/s²), 6 ms
Protection class	IP65
Protection class shaft	IP65


Accessories


RSA-7	1544808
Inlay, outer diameter 38 mm, inner diameter 12 mm	


RSA-11	1545469
Inlay, outer diameter 38 mm, inner diameter 16 mm	


RSA-10	1545465
Inlay, outer diameter 38 mm, inner diameter 25 mm	

RME-5	1544616
 Stainless steel mounting panel for hollow shaft encoders, reference diameter 149 mm, for applications with axial play	

RME-6	1544617
 Stainless steel mounting panel for hollow shaft encoders, reference diameter 104...206 mm, for applications with fixing points on adjustable reference diameter	

RME-10	1544621
 Stainless steel mounting element for hollow shaft encoders, pitch diameter 110 mm, for applications with high axial play	

RME-11	1544622
 Stainless steel mounting element for hollow shaft encoders, pitch diameter 76 mm, for applications with limited mounting space	

RME-15	1544626
 Metal arm bracket, for hollow shaft encoders, length 70 mm; for applications with little axial and radial play; flexibly adjustable	

