


Technical data

Power-on indication	LED, Green
Switching state	LED, Yellow
Error indication	LED, green
Excess gain indication	LED, red
Tests/approvals	
MTTF	67 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE, cURus, CSA

Accessories

SMB30A

3032723




Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread

Technical drawing of SMB30A mounting bracket. Dimensions: 45 (width), 6.3 (hole diameter), 6.3 (width), 38.5 (height), 61 (total height), 69 (base width), 7.5 (base offset), R 40 (radius).

SMB30FAM10

3011185




Mounting bracket, stainless steel, for M10 x 1.5 thread, thread length 30 mm

Technical drawing of SMB30FAM10 mounting bracket. Dimensions: 78.4 (width), 60.3 (hole diameter), 19 (offset), 30.1 (hole diameter), 48 (height), 61.6 (total height), 75 (thread length), M10 (thread).

SMB30SC

3052521



Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable

Technical drawing of SMB30SC mounting bracket. Dimensions: 12.7 (width), 66.5 (height), 58.7 (total height), 50.8 (base width), 29 (base offset), M30 x 1.5 (thread), 7 (hole diameter).