


LX15R

Photoelectric Sensor – Opposed Mode Sensor (Receiver)

Receiver




Technical data

Type	LX15R
ID no.	3071810
Optical data	
Function	Light screen
Operating mode	Receiver
Optical resolution	9.5 mm
Range	150...2000 mm
Scan field	371 mm
Electrical data	
Operating voltage	10...30 VDC
Residual ripple	< 10 % U_{ss}
No-load current	≤ 100 mA
Short-circuit protection	yes
Reverse polarity protection	yes
Output function	NO contact, PNP/NPN
Current output	125 mA
Response time typical	< 4 ms
Mechanical data	
Design	Rectangular, LX
Dimensions	31.8 x 25.4 x 418.2 mm
Housing material	Metal, AL, Grey
Lens	plastic, Acrylic
Electrical connection	Cable, 2 m, PVC
Number of cores	5
Core cross-section	0.5 mm ²
Ambient temperature	-20...+70 °C

Features

- Cable, 2 m, 5-wire
- Protection class IP65
- Scan field 371 mm
- Minimum target size 9.5 mm
- Operating voltage: 10 ... 30 VDC
- Programmable connection for reduced sensing range
- 2 slot nuts including M5 screws for wall mounting included in the scope of delivery

Wiring diagram




Functional principle

Light screens are especially suited to monitor large areas. They consist of an emitter and a receiver unit. Switching light screens are available with scanning heights of up to 599 mm.

Technical data

Relative humidity	0...90 %
Protection class	IP65
Power-on indication	LED, Green
Switching state	LED, Yellow
Error indication	LED, red, Flashing
Tests/approvals	
MTTF	74 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE, cURus



Accessories

SMBLX

3002915

Mounting bracket, galvanized steel, for LX series, 2 pcs., not included in delivery

Technical drawing of the mounting bracket (SMBLX) showing dimensions: $\varnothing 16,2$, 70° , 40° , 1,8, $\varnothing 26,1$, 39,9, 6,4, $\varnothing 4,27$, 12,7, 6,4, 12,7.

SMBLXR

3002914

Foot, galvanized steel, for LX series

Technical drawing of the foot (SMBLXR) showing dimensions: 6,35, 25,4, R 2,6, 23,5, 51,3, 8,9, $\varnothing 63,5$, 5,1, 32, 6,4, 19,1.