

# DS186EQ8

## Photoelectric Sensor

### Technical data

|                              |                                 |
|------------------------------|---------------------------------|
| Type                         | DS186EQ8                        |
| ID no.                       | 3076526                         |
| Optical data                 |                                 |
| Function                     | Opposed mode sensor             |
| Operating mode               | Emitter                         |
| Wavelength                   | 940 nm                          |
| Range                        | 0...20000 mm                    |
| Electrical data              |                                 |
| Operating voltage            | 10...30 VDC                     |
| Residual ripple              | < 10 % U <sub>ss</sub>          |
| DC rated operational current | ≤ 100 mA                        |
| Short-circuit protection     | yes                             |
| Reverse polarity protection  | yes                             |
| Readiness delay              | ≤ 100 ms                        |
| Mechanical data              |                                 |
| Design                       | Rectangular with thread, DS18   |
| Dimensions                   | Ø 18 x 31.1 x 15 x 59.9 mm      |
| Housing material             | Plastic, Thermoplastic material |
| Lens                         | Acrylic                         |
| Electrical connection        | Connectors, M12 × 1, PVC        |
| Number of cores              | 4                               |
| Ambient temperature          | -20...+70 °C                    |
| Protection class             | IP67                            |
| Excess gain indication       | LED                             |
| Tests/approvals              |                                 |



### Features

- Operating voltage: 10...30 VDC

### Wiring diagram

