



# PS001A-502-2UPN8X-H1141 Pressure Transmitter (Rotatable) – 2 PNP/NPN Transistor Switching Outputs



## Features

- Housing is rotatable after plugging the process connection
- Reading of adjusted values without tool
- Recessed pushbutton and keylock for secure programming
- Permanent indication of pressure (bar, psi, kPa, MPa, misc)
- Peak pressure memory
- Pressure range 0...1.0 bar abs.

## Wiring diagram



## Technical data

|                                           |                                  |
|-------------------------------------------|----------------------------------|
| Type                                      | PS001A-502-2UPN8X-H1141          |
| ID                                        | 6832653                          |
| <b>Pressure range</b>                     |                                  |
| Pressure type                             | Absolute pressure                |
| Pressure range                            | 0...1 bar                        |
|                                           | 0...14.5 psi                     |
|                                           | 0...0.1 MPa                      |
| Admissible overpressure                   | ≤ 3 bar                          |
| Burst pressure                            | ≥ 3 bar                          |
| Response time                             | < 3 ms                           |
| <b>Power supply</b>                       |                                  |
| Operating voltage                         | 18...30 VDC                      |
| Current consumption                       | ≤ 50 mA                          |
| Voltage drop at I <sub>o</sub>            | ≤ 2 V                            |
| Protective measure                        | SELV; PELV according to EN 50178 |
| Short-circuit/reverse polarity protection | yes / yes                        |
| Protection type and class                 | IP67<br>IP69K / III              |
| <b>Outputs</b>                            |                                  |
| Output 1                                  | Switching output or IO-Link mode |
| Output 2                                  | Switching output                 |
| <b>Switching output</b>                   |                                  |
| Communication protocol                    | IO-Link                          |
| Output function                           | NO/NC, PNP/NPN                   |
| Accuracy                                  | ± 0.5 % FS BSL                   |

## Functional principle

The pressure sensors in the PS product series operate with ceramic measuring cells. As a result of the pressure acting on the ceramic substrate, a signal that is proportional to the pressure is generated and processed electronically. The processed signal is available either as a switching or an analog output signal, depending on the sensor type used. Maximum flexibility thanks to a rigid or rotatable sensor body, a variety of thread types, front-flush or dead-space-free pressure membranes and an accuracy of 0.5 % of full scale guarantee a safe connection to the process.

## Technical data


|                                                    |                                                                                                                                                                                |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated operational current                          | 0.2 A                                                                                                                                                                          |
| Switching frequency                                | ≤ 180 Hz                                                                                                                                                                       |
| Switching point distance                           | ≥ 0.5 %                                                                                                                                                                        |
| Switch point:                                      | (Min. + 0.005 × range)...100 % of full scale                                                                                                                                   |
| Release point(s)                                   | min up to (SP - 0.005 x range)                                                                                                                                                 |
| Switching cycles                                   | ≥ 100 mil.                                                                                                                                                                     |
| <b>IO-Link</b>                                     |                                                                                                                                                                                |
| IO-Link specification                              | V 1.0                                                                                                                                                                          |
| Programming                                        | FDT / DTM                                                                                                                                                                      |
| Transmission physics                               | corresponds to 3-wire physics (PHY2)                                                                                                                                           |
| Transmission rate                                  | COM 2 / 38.4 kbps                                                                                                                                                              |
| Process data width                                 | 16 bit                                                                                                                                                                         |
| Measured value information                         | 14 bit                                                                                                                                                                         |
| Switchpoint information                            | 2 bit                                                                                                                                                                          |
| Frame type                                         | 2.2                                                                                                                                                                            |
| Accuracy                                           | ± 0.5 % FS BSL                                                                                                                                                                 |
| Included in the SIDI GSDML                         | Yes                                                                                                                                                                            |
| <b>Temperature behaviour</b>                       |                                                                                                                                                                                |
| Medium temperature                                 | -40...+85 °C                                                                                                                                                                   |
| Temperature coefficient zero point TK <sub>0</sub> | ± 0.15 % of full scale/10 K                                                                                                                                                    |
| Temperature coefficient range TK <sub>s</sub>      | ± 0.15 % of full scale/10 K                                                                                                                                                    |
| <b>Environmental conditions</b>                    |                                                                                                                                                                                |
| Ambient temperature                                | -40...+80 °C                                                                                                                                                                   |
| Storage temperature                                | -40...+80 °C                                                                                                                                                                   |
| Vibration resistance                               | 20 g (9...2000 Hz), according to IEC 68-2-6                                                                                                                                    |
| Shock resistance                                   | 50 g (11 ms) acc. to IEC 68-2-27                                                                                                                                               |
| EMV                                                | EN 61000-4-2 ESD: 4 kV CD / 8 kV AD<br>EN 61000-4-3 HF radiated: 15 V/m<br>EN 61000-4-4 Burst: 2 kV<br>EN 61000-4-5 Surge: 1000 V, 42 Ohm<br>EN 61000-4-6 HF cable bound: 10 V |
| <b>Mechanical data</b>                             |                                                                                                                                                                                |
| Housing material                                   | Stainless-steel/Plastic, 1.4305 (AISI 303)                                                                                                                                     |
| Pressure connection material                       | Stainless steel 1.4305 (AISI 303)                                                                                                                                              |
| Pressure transducer material                       | Ceramic Al <sub>2</sub> O <sub>3</sub>                                                                                                                                         |
| Sealing material                                   | FPM spez.                                                                                                                                                                      |
| Process connection                                 | 1/4" NPT-18 female thread                                                                                                                                                      |
| Wrench size pressure connection / coupling nut     | 21/ 30                                                                                                                                                                         |
| Electrical connection                              | Connector, M12 × 1                                                                                                                                                             |
| Max. tightening torque of housing nut              | 35 Nm                                                                                                                                                                          |

Technical data

| Reference conditions acc. to IEC 61298-1 |                                                                                                           |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| Temperature                              | 15...+25 °C                                                                                               |
| Atmospheric pressure                     | 860...1060 hPa abs.                                                                                       |
| Humidity                                 | 45...75 % rel.                                                                                            |
| Auxiliary power                          | 24 VDC                                                                                                    |
| Display                                  | 4-digit 7-segment display, rotatable by 180°, with switch-off function                                    |
| Switching state                          | 2 × LEDs, Yellow                                                                                          |
| Unit display                             | 5 x LEDs green (bar, psi, kPa, MPa, misc)                                                                 |
| Programming options                      | switch/release point, PNP/NPN; NO/NC; hysteresis/window mode, muting; pressure unit, peak pressure memory |
| Tests/approvals                          |                                                                                                           |
| Approvals                                | cULus                                                                                                     |
| UL registration number                   | E183243                                                                                                   |
| MTTF                                     | 439 years acc. to SN 29500 (Ed. 99) 40 °C                                                                 |



Accessories

|                    |       |
|--------------------|-------|
| PTS-COVER          | A9350 |
| Protective housing |       |





Accessories

| Dimension drawing | Type          | ID      |                                                                                                                         |
|-------------------|---------------|---------|-------------------------------------------------------------------------------------------------------------------------|
|                   | WKC4.4T-2/TEL | 6625025 | Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval   |
|                   | RKC4.4T-2/TEL | 6625013 | Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval |

| Dimension drawing                                                                 | Type                | ID      |                                                                                                                               |
|-----------------------------------------------------------------------------------|---------------------|---------|-------------------------------------------------------------------------------------------------------------------------------|
|  | RKC4.4T-2/TXL       | 6625503 | Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PUR, black; cULus approval       |
|  | WKC4.4T-2/TXL       | 6625515 | Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PUR, black; cULus approval         |
|  | RKC4.4T-P7X2-10/TXL | 6626184 | Connection cable, M12 female connector, straight, 4-pin, LED, cable length: 10 m, jacket material: PUR, black; cULus approval |

Accessories

| Dimension drawing                                                                   | Type           | ID      |                                                                                                        |
|-------------------------------------------------------------------------------------|----------------|---------|--------------------------------------------------------------------------------------------------------|
|  | USB-2-IOL-0002 | 6825482 | IO-Link Master with integrated USB port                                                                |
|  | TBEN-S2-4IOL   | 6814024 | Compact multiprotocol I/O module, 4 IO-Link Master 1.1 Class A, 4 universal PNP digital channels 0.5 A |