


# RSC4T-5/TXG

## Actuator and Sensor Cable, PUR – Connection Cable



### Technical data


|                                           |                                        |
|-------------------------------------------|----------------------------------------|
| Type                                      | RSC4T-5/TXG                            |
| ID                                        | 6629672                                |
| Connector A                               | Male, M12 × 1, Straight, A-coded       |
| Number of Pins                            | 3                                      |
| Contacts                                  | Brass, CuZn, Gold-plated               |
| Contact carriers                          | Plastic, TPU, Black                    |
| Connector body                            | Plastic, TPU, Black                    |
| Coupling nut/screw                        | Brass, CuZn, Nickel-plated             |
| Mechanical lifespan                       | > 100 Mating cycles                    |
| Pollution degree                          | 3                                      |
| Protection class                          | IP67, IP69K, Only in screwed condition |
| <b>Cable</b>                              |                                        |
| Cable diameter                            | Ø 4.1 mm ±0.20                         |
| Cable length                              | 5 m                                    |
| Cable jacket                              | PUR, Gray                              |
| Core insulation                           | PP                                     |
| Core cross-section                        | 3 x 0.34 mm <sup>2</sup>               |
| Arrangement of strands                    | 42 x 0.1 mm                            |
| Core colors                               | BN, BU, BK                             |
| <b>Electrical properties at +20 °C</b>    |                                        |
| Rated voltage                             | 250 V                                  |
| Test voltage                              | 2000 V                                 |
| Current                                   | 4 A                                    |
| Insulation resistance                     | > 30.5 MΩ/km                           |
| forward resistance                        | max. 57 Ω/km                           |
| <b>Mechanical and chemical properties</b> |                                        |
| Bending radius (stationary installation)  | ≥ 5 x Ø                                |

### Features



- Male M12, straight, 3-pin
- Jacket material: PUR
- Jacket color: gray
- Suitable for drag chain use
- Resistant to chemicals, UV radiation and oils
- Flame retardant (FT2 acc. to UL 1581, IEC 60332-2-2)
- Resistant to welding sparks
- Free from halogen, silicone, PVC and LABS
- Particularly resistant to abrasion
- Protection class: IP67, IP69K
- Cable length: 5.0 m

### Cable Cross-Section



### Contact assignment

## Technical data

|                                                 |                              |
|-------------------------------------------------|------------------------------|
| Bending radius (flexible use)                   | $\geq 10 \times \varnothing$ |
| Bending cycles                                  | $\geq 5$ million             |
| Admissible acceleration                         | max. 5 m/s <sup>2</sup>      |
| Admissible travel path, horizontal              | 5 m (at 5 m/s <sup>2</sup> ) |
| Admissible travel path, vertical                | 2 m (at 5 m/s <sup>2</sup> ) |
| Admissible traversing speed                     | 3.3 m/s                      |
| Torsional stress                                | $\pm 180^\circ/\text{m}$     |
| Ambient temperature range (stationary)          | -50...+80 °C                 |
| Ambient temperature range (In motion)           | -25...+80 °C                 |
| Ambient temperature during drag chain operation | -25...+60 °C                 |
| Approvals                                       | cULus                        |




## Circuit Diagram




## Accessories

|                                                                                                                       |                |
|-----------------------------------------------------------------------------------------------------------------------|----------------|
| <b>TORQUE-WRENCH-SET-AS</b>                                                                                           | <b>6936170</b> |
| Torque wrench set; handles with adjustable torque 0.4-1.0 Nm, torque wrench for M8 (SW9), fork wrench for M12 (SW 14) |                |


|                                                                                                                                         |                |
|-----------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>BLANK-LABEL-FOR-CORDSETS-TEL-TXL</b>                                                                                                 | <b>6936206</b> |
| Label for TEL and TXL cables, length: 18 mm, height: 4 mm, material: polycarbonate (PC), color: white, halogen-free and flame-retardant |                |




|                                                                                                                                                                                                                            |                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>HA8141-0</b>                                                                                                                                                                                                            | <b>6905407</b> |
| Field-wireable female connector, M12 × 1, straight, 4-pin, insulation piercing connection, cable feedthrough 4.0 to 5.1 mm, core cross-section/terminal capacity 0.14 to 0.34 mm <sup>2</sup> , plastic housing, metal nut |                |




|                                                                                                                                                                                                                          |                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>HA8241-0</b>                                                                                                                                                                                                          | <b>6905401</b> |
| Field-wireable female connector, M12 × 1, angled, 4-pin, insulation piercing connection, cable feedthrough 4.0 to 5.1 mm, core cross-section/terminal capacity 0.14 to 0.34 mm <sup>2</sup> , plastic housing, metal nut |                |




|                                                                                                                                                                                                                         |              |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <b>B8141-0</b>                                                                                                                                                                                                          | <b>69049</b> |
| Field-wireable female connector, M12 × 1, straight, 4-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.14 to 0.75 mm <sup>2</sup> , plastic housing, plastic nut |              |




|                                                                                                                                                                                                                       |              |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| <b>B8241-0</b>                                                                                                                                                                                                        | <b>69048</b> |
| Field-wireable female connector, M12 × 1, angled, 4-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.14 to 0.75 mm <sup>2</sup> , plastic housing, plastic nut |              |



|                                                                                   |                                                                                                                                                                                                          |                                                                                    |                                                                                                                                                                                                        |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BM8141-0                                                                          | 6935145                                                                                                                                                                                                  | BM8241-0                                                                           | 6935889                                                                                                                                                                                                |
|  | Field-wireable female connector, M12 × 1, straight, 4-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.25 to 0.75 mm², plastic housing, metal nut |  | Field-wireable female connector, M12 × 1, angled, 4-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.25 to 0.75 mm², plastic housing, metal nut |

Accessories

| Dimension drawing                                                                 | Type                  | ID        |                                                                                                                                                                            |
|-----------------------------------------------------------------------------------|-----------------------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | LABEL-HOLDER-FLEX-PVC | 100048170 | PVC label holder for identification of extension cables (TEL/TXL product series); for cable diameters: min. 5 mm; dimensions 4 × 18 mm; delivery unit: 50 pcs. per package |