



Inductive Sensor With WeldGuard™ Coating BI20U-CA40-AP6X2-H1141/S1590 W/BS2.0



- Rectangular, height 40 mm
- Variable orientation of active face in 5 directions
- Sensor housing GD-ALSI 12
- Active face PA6-GF30
- Factor 1 for all metals
- Protection class IP67
- Resistant to magnetic fields
- DC 3-wire, 10...30 VDC
- NO contact, PNP output
- M12 x 1 male connector

Wiring Diagram



Functional principle

Inductive sensors detect metal objects contactless and wear-free. For this purpose they use a high-frequency electromagnetic AC field that interacts with the target. The sensors hosting a ferrite core coil generate the AC field through an LC resonant circuit.

Turck WeldGuard sensors are equipped with a thin coating made of thermosetting plastic. This high-tech coating is resistant to abrasion and withstands mechanical stress, as occurring for example in welding systems.

Type	BI20U-CA40-AP6X2-H1141/S1590 W/BS2.0
ID	1627205
Remark to product	Discontinued; Turck Inc. replacement item 1627297 BI20U-CA40-AP6X2-H1141/S1590 W/BS2.0
Special version	S1590 corresponds to: WeldGuard™ coating
General data	
Rated switching distance S_n	20 mm
Mounting conditions	Flush
Secured operating distance	$\leq (0.81 \times S_n)$ mm
Repeat accuracy	$\leq 2\%$ of full scale
Temperature drift	$\leq \pm 10\%$
Hysteresis	3...15 %
Electrical data	
Operating voltage	10...30 VDC
Residual ripple	$\leq 10\% U_{ss}$
DC rated operational current	≤ 200 mA
Residual current	≤ 0.1 mA
Isolation test voltage	≤ 0.5 kV
Short-circuit protection	yes/ Cyclic
Voltage drop at I_L	≤ 1.8 V
Wire breakage/Reverse polarity protection	yes/ Complete
Output function	3-wire, NO contact, PNP
DC field stability	300 mT
AC field stability	300 mT _{ss}
Insulation class	□
Switching frequency	0.25 kHz
Mechanical data	
Design	Rectangular, CA40
Dimensions	65 x 40 x 40 mm variable orientation of active face in 5 directions
Housing material	Metal, GD-ALSi 12
Active area material	Plastic, PA6-GF30, black
Electrical connection	Connector, M12 x 1

Environmental conditions	
Ambient temperature	0...+70 °C
Vibration resistance	55 Hz (1 mm)
Shock resistance	30 g (11 ms)
Protection class	IP67
Power-on indication	LED, Green
Switching state	LED, Yellow
Included in delivery	BS2.0-CK40

Accessories

Type code	Ident no.		Dimension drawing
BSS-CP40	6901318	Mounting clamp for rectangular housings 40 x 40 mm; material: Polypropylene	