


# TL30FBYGQ


## LED Indicator – Multicolor/Multifunction Display



### Features

- Plastic housing, black
- EMI and RFI immune
- Protection class IP65
- M12 x 1 connector
- Colors: Blue (COL 1) / Yellow (COL 2) / Green (COL 3)
- Operating voltage: 18...30 VDC or 24 VAC with 45 mA per LED color
- Inputs: PNP/NPN

### Wiring diagram



### Functional principle

Flat multicolor/multifunction display  
 Rugged and well-priced LED tower, easy to install  
 Illuminated segments for clear operator guidance and display of system status  
 Display of up to 5 colors  
 Compact devices, no controller required  
 No mounting  
 The wiring diagram shows a PNP pin assignment



### Technical data

Type	TL30FBYGQ
ID	3086632
<b>Signal and display data</b>	
Purpose	LED indicator light
Function	Tower light
Light type	Blue Yellow Green
Dimmable	No
Features of color 1	Blue, Permanently on
Features of color 2	Yellow
Features of color 3	Green
<b>Electrical data</b>	
Operating voltage	18...30 VDC
DC rated operational current	≤ 18 mA
Operating voltage	21...27 VAC
Max. current consumption per color	18 mA
Input type	Bipolar (PNP/NPN)
Response time typical	< 1 ms
<b>Mechanical data</b>	
Cascadable	No
Design	Rectangular, TL30F
Dimensions	128.1 x 30 x 19.1 mm
Housing material	Metal, AL Thermoplastic material, Black
Window material	Acrylic, diffuse
Electrical connection	Connector, M12 × 1, PVC
Number of cores	4



## Technical data

Ambient temperature	-40...+50 °C
Relative humidity	0...95 %
Protection class	IP65
<b>Tests/approvals</b>	
Approvals	CE

## Accessories

<b>SMBPVA1</b>	<b>3056884</b>	<b>SMBPVA2</b>	<b>3054451</b>
 <p>Mounting bracket, for PVA and PVD, stainless steel; set consisting of two brackets and screws</p>		 <p>Mounting bracket, for PVA and PVD, for mounting on 28 mm pipes, 4 brackets (2 per sensor) included in delivery</p>	

## Accessories

Dimension drawing	Type	ID	
	RKC4.4T-2/TEL	6625013	Connection cable, M12 female connector, straight, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval
	WKC4.4T-2/TEL	6625025	Connection cable, M12 female connector, angled, 4-pin, cable length: 2 m, jacket material: PVC, black; cULus approval