

TX700 HMI/PLC Series

5" Display - CODESYS V3 PLC with TARGET and WEB VISU High-Quality Metal Housing and Glass Front with a Capacitive Touch

TX705-P3CV01








- 5" TFT wide screen color display
- LED backlight
- 800 x 480 pixel resolution
- 64 K colors
- Capacitive touchscreen with glass front
- 2 separated RJ45 Ethernet ports with 10/100 Mbit
- 1 serial interface (RS232, RS485, RS422)
- 1 USB host port
- 1 SD card slot

Type	TX705-P3CV01
ID	100002029
Display/touch	
Display	TFT colour
Touchscreen	Capacitive, Glass front
Active screen area	5"
Resolution (pixels)	800 × 480 WVGA
Format	16:9
Brightness	300 cd/m² typ.
dimmmable	Yes, To 0 %
Controller	
Processor	ARM Cortex A8, 1 GHz
Memory	4 GB Flash
RAM memory	512 MB
Add-on memory	1 x SD card slot, 1 x USB host port
Real time clock	Yes (battery-buffered)
PLC data	
Programming	CODESYS V3
Released for CODESYS version	V 3.5.12.10
Programming languages	IEC 61131-3 (IL, LD, FBD, SFC, ST)
Programming interface	Ethernet
Program memory	20000 kByte
Non-volatile memory	63 kByte


Interfaces	
Onboard	2 × RJ45 Ethernet, 1 × RS232/485/422, 1 × USB host, 1 × power supply, 2 × expansion slot
Onboard for selection	CANopen Master (via extension module)
Ethernet	2 x 10/100 Mbit
Protocols	PROFINET (Controller/Master) EtherNet/IP (Scanner/Master) Modbus TCP (Master/Slave) EtherCAT (Master)
Fieldbus	Modbus RTU (Master/Slave) CANopen (Master)
USB	1 × host port
Serial	RS232 / RS485 / RS422
Expansion slot	One slot for up to two plug-in modules
Power supply	
Rated value	24 VDC, max. 0.6 A
Admissible voltage range	10...32 VDC
General data	
Operating ambient conditions	-20...60 °C, 5...85 % relative humidity, non-condensing
Storage ambient conditions	-30...70 °C, 5...85 % relative humidity, non-condensing
Approvals	CE cULus LR DNV GL
Ex approval	ATEX IEC Ex Haz. Loc. Class I, Division 2, Groups A,B,C and D
Protection class	IP66 front, IP20 rear NEMA type: 12/4X
Dimensions	
Front (W x H x D)	147 x 107 x 52 mm
Cut-out (W x H)	136 x 96 mm
Mounting depth	52+8 mm
Weight	approx. 1.2 kg

Connection and pin assignment

	Power Supply The power supply connector is delivered with each device. It can be reordered at Turck as accessories. Type designation: TX-Mount-xx	Pin Assignment  1 = 24 VDC 2 = 0 V 3 = $\frac{1}{2}$
	USB Interface	Pin Assignment  1 = 5 VDC 2 = D⁻ 3 = D⁺ 4 = GND
	Ethernet Ports The Ethernet ports are independent. Ethernet cables (examples): RJ45 male connector – RJ45 male connector: RJ45S-RJ45S-4414-2M (Order number: 6441423) RJ45 male connector – M12 male connector, 4-pin, D-coded: RSSD-RJ45S-4414-2M (Order number: 6441413) RJ45 male connector – M8 male connector, 4-pin: PSGS4M-RJ45S-4414-2M (Order number: 6933005) RJ45 male connector – M12 female receptacle, 4-pin, D-coded: RJ45-FKSD-4414-2M (order number: 6935282)	Pin Assignment  1 = TX⁺ 2 = TX⁻ 3 = RX⁺ 4 = n.c. 5 = n.c. 6 = RX⁻ 7 = n.c. 8 = n.c.
	Serial Interface The serial interface can be operated either as RS232, RS485 or RS422. The adjacent wiring diagrams show the respective pin assignments. PLEASE NOTE: In RS485 mode, pins 1 and 2 as well as 3 and 4 must be externally connected!	Pin Assignment in RS232 Operating Mode  1 = RX 2 = TX 3 = CTS 4 = RTS 5 = +5 VDC output 6 = GND 7 = n.c. 8 = shield Pin Assignment in RS485 Operating Mode  1 = B⁻ (RX⁻) 2 = A⁻ (TX⁻) 3 = B⁺ (RX⁺) 4 = A⁺ (TX⁺) 5 = +5 VDC output 6 = GND 7 = n.c. 8 = shield Pin Assignment in RS422 Operating Mode  1 = RX⁻ 2 = TX⁻ 3 = RX⁺ 4 = TX⁺ 5 = +5 VDC output 6 = GND 7 = n.c. 8 = shield



Port for Plug-in Module



SD Card Slot

SD card (example): SD CARD 2 GB (order number: 6828025)

Accessories

Type code	Ident no.		Dimension drawing
TX700-MOUNT-07	100003188	TX700 mounting bracket and power connectors for 5–7" devices	
TX-LTE-WLAN	100025179	Plug-in LTE and Wi-Fi modem with LTE/UMTS/GSM, Wi-Fi and GNSS	

Function accessories

Type code	Ident no.		Dimension drawing
TX-IO-XX03	6828201	Plug-in I/O module — 20 DI, 12 DO, 4 AI (U/I/RTD/TC), 4 AO (U/I)	
TX-IO-DX06	6828203	Plug-in I/O module — 8 DI, 6 DO, 1 relay output (NO)	
TX-EXTEND	100004786	Plug-in extension module for mechanical adjustment for using the TX-IO-XX03 module	

Function accessories

Type code	Ident no.		Dimension drawing
TX-UMTS	100009535	Plug-in radio modem with 2G/3G support	
TX-DP-S	100010167	Plug-in PROFIBUS DP slave interface, 9-pin SUB-D female connector	
TX-CAN	6828210	Plug-in CANopen interface, 9-pin SUB-D male connector	
TX-RS485	100002598	Plug-in interface for RS485/RS422, 9-pin SUB-D female connector	
TX-RS232	100002599	Plug-in interface for RS232, 9-pin SUB-D female connector	

Function accessories

Type code	Ident no.		Dimension drawing
TX-PSC	100002938	Power Supply Male Connector for TX HMI Devices	