

B-TL70DXN2-8 LED Indicator – Modular Signal Tower Base Module with Integrated Wireless Receiver



Technical data

-			
Туре	B-TL70DXN2-8		
	3094216		
Signal and display data			
Purpose	LED indicator light		
Function	Tower light		
Dimmable	No		
Electrical data			
Operating voltage	1230 VDC		
Max. current consumption per color	420 mA		
Input type	PNP		
Response time typical	< 180 ms		
Mechanical data			
Cascadable	No		
Design	Smooth barrel, TL70		
Dimensions	Ø 70 x 47.5 mm		
Housing material	Plastic, PC, Black		
Electrical connection	Connector, M12 × 1, 2 m, PVC		
Number of cores	8		
Ambient temperature	-40+50 °C		
Relative humidity	095 %		
Protection class	IP65		
Tests/approvals			
Approvals	CE, UL listed		



Features

Plastic housing, black	
Protection class IP65	

- Protection against electromagnetic and
- high-frequency interference
- Cable, PVC, 2 m, 8-wire
- End element included in the delivery
- Operating voltage: 12...30 VDC
- Integrated radio module
- DX80-compatible node
- Configuration via DIP switch

Wiring diagram



Functional principle

The rugged multifunction tower lights are available in many variations and are easily mounted. Each tower can be assembled of up to five color segments and, optionally, a beeper. All segments are configurable via DIP switches.

5 colors ar available, blue (B), green (G), red (R), yellow (Y) and white (W), which can be used in any combination.



The arrangement of the segments can be modified subsequently and also more segments can be added. Via the basic module the respective port is selected. The wiring diagram shows a PNP pin assignment.



Accessories

Dimension drawing	Туре	ID	
• 72 - D	SG-TL70-G	3092211	TL70 color segment, color: Green
. n. O	SG-TL70-Y	3092212	TL70 color segment, color: Yellow
a 70 - 50 - 50	SG-TL70-R	3092213	TL70 color segment, color: Red
	SG-TL70-B	3092214	TL70 color segment, color: Blue
* 70 - O	SG-TL70-W	3092215	TL70 color segment, color: White
• 72 - 1 2 - 1 2	SG-TL70-A	3092221	TL70 audio segment, black