


Actuator and Sensor Cable, PUR Quick-turn Connection Cable WKC4Q-10/TXL




- Female M12, angled, 3-pin
- Sheath material: PUR
- Sheath color: black
- Qualified for drag chain use
- Resistant to weld splatter
- Resistant to chemicals, UV radiation and oils
- Flame retardant
- Free from halogen, silicone, PVC and LABS
- Particularly resistant to abrasion
- RoHS conform
- Protection class IP67
- Cable length: 10 m


Type	WKC4Q-10/TXL
ID	6628015
Connector A	Female, M12 × 1, Angled, A-coded
Number of Pins	3
Contact carriers	Plastic, TPU, Black
Connector body	Plastic, TPU, Yellow
Interlocking sleeve	Plastic, PBT, black
Mechanical lifespan	> 50 Mating cycles
Pollution degree	3
Protection class	IP67, (plugged)

Cable	
Cable diameter	Ø 4.1mm ±0.20
Cable length	10 m m
Cable jacket	PUR, Black
Core insulation	PP
Core cross-section	3 x 0.34 mm²
Arrangement of strands	42 x 0.1mm
Core colors	BN, BU, BK

Electrical properties at +20 °C	
Rated voltage	250V
Test voltage	2000 V
Current	4AA
Insulation resistance	> 30.5 MΩ/km
forward resistance	max. 57 Ω/km








Circuit Diagram



Mechanical and chemical properties	
Bending radius (stationary installation)	$\geq 5 \times \varnothing$
Bending radius (flexible use)	$\geq 10 \times \varnothing$
Bending cycles	≥ 5 million
Admissible acceleration	max. 5 m/s ²
Admissible travel path, horizontal	5 m (at 5 m/s ²)
Admissible travel path, vertical	2 m (at 5 m/s ²)
Admissible traversing speed	3.3 m/s
Torsional stress	$\pm 180^\circ/\text{m}$
Ambient temperature range (stationary)	-50...+80°C
Ambient temperature range (In motion)	-25...+80°C
Ambient temperature during drag chain operation	-25...+60°C

Accessories

Type code	Ident no.		Dimension drawing
HAS8141-0	6905406	Field-wireable male connector, M12 × 1, straight, 4-pin, insulation piercing connection, cable feedthrough 4.0 to 5.1 mm, core cross-section/terminal capacity 0.14 to 0.34 mm², plastic housing, metal nut	 Technical drawing of the HAS8141-0 connector. It is a straight, 4-pin male connector with an M12 × 1 thread. The drawing shows a side view with dimensions: overall length ≈ 46.8 mm, outer diameter ø 15.3 mm, and pin spacing 14 mm and 13 mm. The label 'M12 x 1' is also present.
HAS8241-0	6905400	Field-wireable male connector, M12 × 1, angled, 4-pin, insulation piercing connection, cable feedthrough 4.0 to 5.1 mm, core cross-section/terminal capacity 0.14 to 0.34 mm², plastic housing, metal nut	 Technical drawing of the HAS8241-0 angled connector. It features an M12 × 1 thread and a 4-pin configuration. Dimensions shown include an overall length of 38.9 mm, an outer diameter of ø 15 mm, and a mounting height of 32.5 mm. Pin spacing of 13 mm is indicated. The label 'M12 x 1' is included.
BS8141-0	69010	Field-wireable male connector, M12 × 1, straight, 4-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.14 to 0.75 mm², plastic housing, metal retaining screw	 Technical drawing of the BS8141-0 straight connector with screw terminals. It has an M12 × 1 thread. Dimensions include an overall length of ≈ 60.4 mm, an outer diameter of ø 20.2 mm, and pin spacing of 18 mm, 14 mm, and 13 mm. The label 'M12 x 1' is shown.
BS8241-0	69011	Field-wireable connector, M12 × 1, angled, 4-pin, screw terminal connection, cable feedthrough 4.0 to 6.0 mm, core cross-section/terminal capacity 0.14 to 0.75 mm², plastic housing, metal retaining screw	 Technical drawing of the BS8241-0 angled connector with screw terminals. It features an M12 × 1 thread. Dimensions shown are an overall length of 42.6 mm, an outer diameter of ø 20.2 mm, and a mounting height of ≈ 33 mm. Pin spacing of 18 mm, 18 mm, and 13 mm is indicated. The label 'M12 x 1' is present.
BLANK-LABEL-FOR-CORDSETS-TEL-TXL	6936206	Label for TEL and TXL cables, length: 18 mm, height: 4 mm, material: polycarbonate (PC), color: white, halogen-free and flame-retardant	 Technical drawing of the BLANK-LABEL-FOR-CORDSETS-TEL-TXL label. It is a rectangular label with a length of 18 mm and a height of 4 mm.