REM-104HA3E-3C13S12M-H1181
Absolute Rotary Encoder - Multiturn
Industrial Line



Features

- Flange with stator coupling, Ø 63 mm
- Hollow shaft, Ø 12.7 mm
- Optical measuring principle
- Shaft material: stainless steel
- Protection class IP67 on housing and shaft side
- -40…+85 °C
- Max. 4000 rpm (continuous operation 2000 rpm)
- 10…30 VDC
- SSI, gray
- M12 × 1 male, 8-pin
- Singleturn, 13-bit resolution
- Multiturn, 12-bit resolution

Technical data

Type	REM-104HA3E-3C13S12M-H1181
ID	100011395
Measuring principle	Optical
General data	
Max. Rotational Speed	4000 rpm
Moment of inertia of the rotor	6 × 10^{-6} kgm²
Starting torque	< 0.05 Nm
Absolute accuracy	± 0.015 ° At 25 °C
Output type	Absolute multiturn
Resolution singleturn	13 Bit
Resolution multiturn	12 Bit
Electrical data	
Operating voltage	10…30 VDC
No-load current	30 mA
Short-circuit protection	yes
Wire breakage/Reverse polarity protection	yes
Communication protocol	SSi
Output function	Gray coded
Mechanical data	
Design	Hollow shaft
Flange type	Flange with stator coupling
Flange diameter	Ø 63 mm
Shaft Type	Hollow shaft
Shaft diameter D [mm]	12.7
Shaft material	Stainless steel

Wiring diagram





REM-104HA3E-3C13S12M-H1181| 07-11-2023 22-17 | Technical modifications reserved

Technical data

Housing material	Die-cast zinc
Electrical connection	Connector, M12 × 1
	M12, 8-pin
Axial shaft load	40 N
Radial shaft load	80 N
Environmental conditions	
Ambient temperature	-40…+85 °C
Vibration resistance (EN 60068-2-6)	100 m/s², 10…2000 Hz
Shock resistance (EN 60068-2-27)	2500 m/s², 6 ms
Protection class	IP67
Protection class shaft	IP67

Accessories

Dimension drawing	Type	ID	
	E-RKC 8T-264-2	U-04781	Connection cable, female M12, straight, 8-pin (twisted pairs),shielded, cable length: 2 m, sheath material: PVC, black; cULus approval; other cable lengths and qualities available, see www.turck.com

REM-104HA3E-3C13S12M-H1181| 07-11-2023 22-17 | Technical modifications reserved