

# PT10V-1104-I2-H1141

## Pressure Transmitter – With Current Output (2-Wire)





### Features

- For mobile hydraulic applications
- Ceramic measuring cell
- Compact and robust design
- Excellent EMC properties
- Excellent accuracy and long-term stability
- Complies with ISO 16750-2
- Pressure range -1...10 bar rel.
- 7.5...33 VDC
- Analog output 4...20 mA
- Process connection G1/4" male thread (back sealing) according to DIN EN ISO 1179-2 with FPM profile sealing ring
- Connector device, M12 × 1

### Technical data

|                                           |                                                   |
|-------------------------------------------|---------------------------------------------------|
| Type                                      | PT10V-1104-I2-H1141                               |
| ID                                        | 100021182                                         |
| <b>Pressure range</b>                     |                                                   |
| Pressure type                             | Relative pressure                                 |
| Pressure range                            | -1...10 bar                                       |
|                                           | -14.5...145.04 psi                                |
|                                           | -0.1...1 MPa                                      |
| Admissible overpressure                   | ≤ 25 bar                                          |
| Burst pressure                            | ≥ 25 bar                                          |
| Response time                             | < 2 ms, typ. 1 ms                                 |
| Long-term stability                       | 0.3 % FS, acc. to IEC EN 61298-2                  |
| <b>Power supply</b>                       |                                                   |
| Operating voltage                         | 7.5...33 VDC                                      |
| Current consumption                       | ≤ 23 mA                                           |
| Short-circuit/reverse polarity protection | yes / yes                                         |
| Protection type and class                 | IP69K / III                                       |
| Insulation voltage                        | 500 VDC                                           |
| <b>Outputs</b>                            |                                                   |
| Output 1                                  | Analog output                                     |
| Output function                           | Analog output current                             |
| <b>Analog output</b>                      |                                                   |
| Current output                            | 4...20 mA                                         |
| Load                                      | ≤ (Supply voltage - 7.5) / 20 kΩ                  |
| Accuracy LHR                              | ±0.5 % FS (under EMC interference max. ±1.5 % FS) |
| <b>Temperature behaviour</b>              |                                                   |
| Medium temperature                        | -40...+125 °C                                     |

### Wiring diagram



### Functional principle

The pressure sensors in the PT...-1100 product series are designed specifically for demanding mobile hydraulic applications. They operate with a ceramic measuring cell in different pressure ranges of up to 0...60 bar in 2- or 3-wire technology. Depending on the sensor variant, the processed signal is available as an analog output signal (4...20 mA, 0...10 V, 0...5 V, ratiometric). A wide range of process connections and electrical connections offer a high degree of flexibility in a wide range of applications.

## Technical data

|                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature coefficient                         | ± 0.2 % of full scale/10 K                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Environmental conditions</b>                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Ambient temperature                             | -40...+100 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Storage temperature                             | -50...+100 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Vibration resistance                            | Test VI (12 g, sinusoidal 18 g random vibration)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Shock resistance                                | 50 g, 11 ms, half sine curve, 1000x/axis acc. to ISO 16750-3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| EMV                                             | Interference Immunity/Interference Emission<br>EN 61326-2-3 - Pressure transducer<br>ISO 13766 - Earthmoving machinery<br>DIN EN 13309 - Construction machinery<br>DIN ISO 14982 - Forestry and agriculture<br>Motor vehicle directive ECE R10<br>Motor vehicle directive 2004/104/EC<br>Immunity Motor Vehicle Directive<br>ISO 11452-2, HF (Field), 100 V/m (200... 2000 MHz)<br>ISO 11452-4, HF (BCI), 100 mA (20... 400 MHz)<br>ISO 10605, ESD, ±8 kV contact, ±15 kV air<br>ISO 7637-2, pulses 1, 2a, 2b, 3a, 3b (test level 4)<br>ISO 16750-2, load dump, 155 V (1 Ω, 300 ms)<br>Interference Emission Motor Vehicle Directive<br>CISPR25 |
| <b>Mechanical data</b>                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Housing material                                | Stainless-steel/Plastic, 1.4404 (AISI 316L)/polyarylamide 50 % GF UL 94 V-0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Pressure connection material                    | Stainless steel 1.4404 (AISI 316L)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Pressure transducer material                    | Ceramic Al <sub>2</sub> O <sub>3</sub>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Sealing material                                | FPM spez.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Process connection                              | G1/4" male thread (back sealing) according to DIN EN ISO 1179-2 with FPM profile sealing ring                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Wrench size pressure connection / coupling nut  | 24                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Electrical connection                           | Connector, M12 × 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Max. tightening torque of housing nut           | 20 Nm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>Reference conditions acc. to IEC 61298-1</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Temperature                                     | 15...+25 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Atmospheric pressure                            | 860...1060 hPa abs.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Humidity                                        | 45 % rel.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Auxiliary power                                 | 24 VDC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

Technical data

| Tests/approvals      |                                            |
|----------------------|--------------------------------------------|
| MTTF                 | 1189 years acc. to SN 29500 (Ed. 99) 40 °C |
| Included in delivery | Profile seal FKM special (1 pc)            |