


# TL50GYRCQ

## LED Indicator – Tower Light




### Technical data

|                                    |                              |
|------------------------------------|------------------------------|
| Type                               | TL50GYRCQ                    |
| ID                                 | 3015117                      |
| Signal and display data            |                              |
| Purpose                            | LED indicator light          |
| Function                           | Tower light                  |
| Light type                         | Green<br>Yellow<br>Red       |
| Dimmable                           | No                           |
| Features of color 1                | Green, Permanently on, 23 lm |
| Features of color 2                | Yellow, Permanently on, 5 lm |
| Features of color 3                | Red, Permanently on, 7.5 lm  |
| Operating voltage                  | 18...30 VDC                  |
| DC rated operational current       | ≤ 45 mA                      |
| Operating voltage                  | 21...27 VAC                  |
| AC rated operational current       | ≤ 45 mA                      |
| Max. current consumption per color | 45 mA                        |
| Input type                         | Bipolar (PNP/NPN)            |
| Response time typical              | < 10 ms                      |
| Mechanical data                    |                              |
| Cascadable                         | No                           |
| Design                             | Smooth barrel, TL50          |
| Dimensions                         | Ø 50 x 169.9 mm              |
| Housing material                   | Plastic, ABS, Grey           |
| Window material                    | Polycarbonate, diffuse       |
| Electrical connection              | Connector, M12 × 1, PVC      |
| Number of cores                    | 4                            |

### Features

- Plastic housing, black
- EMI and RFI immune
- Protection class IP67
- M12 × 1 male connector
- Multicolor: Green (COL 1) / Yellow (COL 2) / Red (COL 3)

### Wiring diagram



### Functional principle

The TL50 tower lights provide highly visible status indicators and a clear user guidance within the entire system. They can be assembled from varicolored LEDs and are available with or without beeper. You can mount them directly on machines, in the cabinet or in monitoring locations of production lines.

The wiring diagram shows a PNP pin assignment.

There are 10 colors available blue (B), green (G), red (R), yellow (Y), white (W), turquoise (T), orange (O), violet (V), sky blue (S) and magenta (M), which specify the light sequence from bottom to top in the type code of the tower light. Example: TL50GYRQ, colors green, yellow and red arranged from bottom to top.

