

K50LBXA1XPQP
LED Indicator – Beacon



Technical data

Type	K50LBXA1XPQP
ID	3801115
Signal and display data	
Purpose	LED indicator light
Function	Spotlight
Light type	Blue
Dimmable	No
Features of color 1	Blue, Permanently on
Acoustic signal	Continuous tone, 75 dB
Special features	Wash down
Electrical data	
Operating voltage	18...30 VDC
DC rated operational current	≤ 40 mA
Max. current consumption per color	40 mA
Max. current consumption of beeper	40 mA
Input type	PNP
Response time typical	< 10 ms
Mechanical data	
Cascadable	No
Design	Dome, K50L
Dimensions	Ø 50 x 57 mm
Housing material	Plastic, PC ABS, Black
Window material	Polycarbonate, diffuse
Electrical connection	Cable with connector, M12 × 1, 0.15 m, PVC
Number of cores	5

Features

- LED all-round visible
- Individually controllable
- Screw-in thread M30x1.5
- Protection class IP67
- Monochrome: Blue (COL 1)
- Cable with male end M12 x 1
- Operating voltage 18...30 VDC

Wiring diagram

Keine Maßzeichnung
vorhanden!

No drawing available!


Technical data

Ambient temperature	-20...+50 °C
Relative humidity	0...90 %
Protection class	IP50
Tests/approvals	
MTTF	249 years acc. to SN 29500 (Ed. 99) 40 °C
Approvals	CE, UL listed

Accessories

SMB30A 3032723

Mounting bracket, rectangular, stainless steel, for sensors with 30mm thread



SMB30SC 3052521

Mounting bracket, PBT black, for sensors with 30 mm thread, rotatable

